



Max. Depth	500 m	6000 m
Number of Ports	3	3
Biofouling Protection	Street Lamp UV (Optional)	N/A
GPS	LGR: Yes RTS: No XC: No	LGR: No RTS: No XC: No
Communication	LGR: WiFi, USB-C RTS: RS232 XC: WiFi, RS232 & USB-C	LGR: USB-C RTS: RS232 XC: RS232 & USB-C
Input Voltage	8-30 VDC	8-30 VDC
Pressure Housing	Acetal	Titanium
Protective Cage	Stainless Steel	Stainless Steel
Dimensions	Sm Cage: 343 x 76 mm Md Cage: 398 x 76 mm Lg Cage: 464 x 76 mm	Sm Cage: 343 x 76 mm Md Cage: 398 x 76 mm Lg Cage: 464 x 76 mm
Weight in Air	1.4 kg	2.5 kg
Weight in Water	0.7 kg	1.9 kg
Software	Sailfish	Sailfish

## Key Benefits:

- **Three X2•Series Interchangeable Ports:** Ability to custom configure a single instrument for multiple applications
- **Magnetic On/Off Switch:** Configure now, power and deploy later (LGR & XC version only)
- **Integrated WiFi & GPS:** Transfer data wirelessly (LGR 500 m version only)
- **USB Connectivity:** Recharge battery and connect via USB (LGR & XC version only)
- **Integrated UV Biofouling:** Maintain consistent data quality & decrease maintenance intervals (Optional on RTS & XC 500 m version only)
- **Sailfish Software:** Configure, download, process, and export profiles automatically